



LiteFLEX™ Datasheet

Description:	LiteFLEX™ is a 400gsm coated PVC developed by HVG using the highest quality resins, UV stabilisers and inhibitors.
Application:	Tarpaulins, general covers, swag bases, tent floors, campervans, tool bags, sporting equipment and fumigation covers.
Weight:	400gsm
Width:	300cm
Roll Length:	30m
Construction:	550 dtex x 1100 dtex, Single Ripstop
Composition:	Coated both sides with PVC, woven polyester scrim
Colours:	Black, Grey, Charcoal, Yellow, White (Matt Laq Finish)
Coating:	Coated PVC
Fabric Finish:	Matt top side/Gloss underside
Tensile Strength:	Warp 1700N/5cm, Weft 1600N/5cm
Tear Strength:	Warp 270N/5cm, Weft 160N/5cm
Weld Adhesion:	80N/5cm
Temperature Range:	-30°C +70°C
UV Resistant:	Yes
Warranty:	Yes – 2 year UV Warranty
Printability:	UV (Latex subject to customer confirmation)

Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.

CD1023

SYDNEY
 29 Henderson Street
 Turrella NSW 2205

MELBOURNE
 25 West Park Drive
 Derrimut VIC 3026

BRISBANE
 128 Mica Street
 Carole Park QLD 4300

PERTH
 72 Bushland Ridge
 Bibra Lake WA 6163

ADELAIDE
 57 Barnes Avenue
 Marleston SA 5033

